

MA-DBO2458-6

2.3-2.7 GHz & 4.9-6.0 GHz Dual Band Omni Antenna

MARS Dual Band Omni antenna provides coverage of 2.3 to 2.7 GHz & 4.9 to 6.0 GHz in a single antenna radome.

Additional Features:

- Simultaneous coverage of LTE & 802.11 a, b, e, g, n, WiMAX & 4.9 GHz Public Safety Bands.
- Light weight and durable construction.
- UV protected radome.



Specifications

Electrical

Frequency range	2.3-2.7 GHz & 4.9-6.0 GHz
GAIN, typ.	4 dBi @ 2.3-2.7 GHz 5 dBi @ 2.4-2.5 GHz 7 dBi @ 4.9-6.0 GHz
VSWR, max.	2 : 1
Polarization	Linear Vertical
Input power, max.	10 Watt
Input Impedance	50 Ohm

Mechanical

Dimensions (HxDia.)	210 x 28.5 mm (8.3" x 1.1")
Connector	See Ordering Options
Weight	90 gr.
Radom	UV Protected Plastic
Mount	See Ordering Options

Environmental

Operating Temperature Range	-40°C to +70°C
Vibration	According to IEC 60721-3-4
Water Proofing	IP-67
Flammability	UL94
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)

Ordering Options

MA-DBO2458-6	Antenna with RP N-Type Plug connector
MA-DBO2458-6NF	Antenna with N-Type Female connector
MA-DBO2458-6NM	Antenna with N-Type Male connector
MA-DBO2458-6NF1	Antenna with N-Type Female connector with mount

Patterns are available on our website

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 58861, P.O.Box 5 AZOR 58008, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com