




## Round Member Adapter

These stainless steel Round Member Adapters are used to mount hangers, clamp heads, and Standoff Brackets to round members.

Item #	Description	Wt. lb.	Wt. kg.
C20-121-001	Less than 2" OD (50.8 mm) pipe (10 per package)	0.60	0.27
C20-121-002	Less than 3" OD (76.2 mm) pipe (10 per package)	0.60	0.27
C20-121-003	Less than 4" OD (101.6 mm) pipe (10 per package)	0.81	0.37
C20-121-004	Less than 5" OD (127 mm) pipe (10 per package)	0.83	0.38
C20-121-005	Less than 6" OD (152.4 mm) pipe (10 per package)	0.94	0.43
C20-121-006	Less than 7" OD (177.8 mm) pipe (10 per package)	1.07	0.49



## Fillister-Head Screw Assembly Hardware

Each assembly includes one (1) Fillister-Head Screw, one (1) Hex Nut and one (1) Toothed Lock Washer. Each package includes ten (10) Fillister-Head Screw Assemblies.

Item #	Description	Wt. lb.	Wt. kg.
C40-013-013	$\frac{3}{8}$ " diameter x $\frac{3}{4}$ " long (9.53 mm x 19.05 mm) (10 per package)	0.70	0.32
C40-013-014	$\frac{3}{8}$ " diameter x 1" long (9.53 mm x 25.4 mm) (10 per package)	1.10	0.50



## Weathershield

Accommodates both N and DIN connectors, and provides a watertight seal at all connections by dampening vibrations at connector interfaces. A quick solution, the Weathershield installs in seconds with no tape or mastic required. Sold individually, one per connection is required.

Item #	Description	Wt. lb.	Wt. kg.
C40-114-001	$\frac{1}{2}$ " (12.7 mm) to antenna connection	0.35	0.16
C40-114-002	$\frac{1}{2}$ " to $\frac{7}{8}$ " (12.7 mm to 22.22 mm) connections	0.55	0.25
C40-114-003	$\frac{1}{2}$ " to $1\frac{1}{4}$ " (12.7 mm to 31.75 mm) connections	0.75	0.34
C40-114-004	$\frac{1}{2}$ " to $1\frac{5}{8}$ " (12.7 mm to 41.28 mm) connections	0.95	0.43

**Looking for more?**

**Visit [www.SabreSiteSolutions.com](http://www.SabreSiteSolutions.com).**

If you have a project that requires something special, give us a call at **866-428-6937**.

We will research and find it for you. We want to make sure that you have all the components necessary to meet your project requirements.