

Product Specifications

FSJ1-50A

FSJ1-50A, HELIAX[®] Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket



CHARACTERISTICS

Construction Materials

Jacket Material	PE
Outer Conductor Material	Corrugated copper
Dielectric Material	Foam PE
Flexibility	Superflexible
Inner Conductor Material	Copper-clad aluminum wire
Jacket Color	Black

Dimensions

Nominal Size	1/4 in
Cable Length	0 km
Cable Weight	0.05 lb/ft 0.07 kg/m
Diameter Over Dielectric	4.826 mm 0.190 in
Diameter Over Jacket	7.366 mm 0.290 in
Inner Conductor OD	1.9050 mm 0.0750 in
Outer Conductor OD	6.350 mm 0.250 in

Electrical Specifications

Cable Impedance	50 ohm \pm 1 ohm
Capacitance	24.2 pF/ft 79.4 pF/m
dc Resistance, Inner Conductor	3.000 ohms/kft 9.843 ohms/km
dc Resistance, Outer Conductor	2.000 ohms/kft 6.562 ohms/km
dc Test Voltage	1600 V
Inductance	0.200 μ H/m 0.061 μ H/ft
Insulation Resistance	100000 MOhm
Jacket Spark Test Voltage (rms)	5000 V
Operating Frequency Band	1 – 18000 MHz

www.commscope.com/andrew

Product Specifications



FSJ1-50A

Peak Power	6.4 kW
Pulse Reflection	1%
Velocity	84%

Environmental Specifications

Installation Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-70 °C to +85 °C (-94 °F to +185 °F)

General Specifications

Brand	HELIAX®
-------	---------

Mechanical Specifications

Bending Moment	1.1 N-m 0.8 ft lb
Flat Plate Crush Strength	100.0 lb/in 1.8 kg/mm
Minimum Bend Radius, Multiple Bends	25.40 mm 1.00 in
Minimum Bend Radius, Single Bend	25.40 mm 1.00 in
Number of Bends, minimum	15
Number of Bends, typical	20
Tensile Strength	68 kg 150 lb

Standard Conditions

Attenuation, Ambient Temperature	20 °C 68 °F
Average Power, Ambient Temperature	40 °C 104 °F
Average Power, Inner Conductor Temperature	100 °C 212 °F

www.commscope.com/andrew

©2011 CommScope, Inc. All rights reserved.
All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope. All specifications are subject to change.
See www.commscope.com/andrew for the most current information.

page 2 of 4
2/7/2011

Product Specifications

FSJ1-50A



Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Average Power (kW)
0.5	0.407	0.124	6.40
1	0.577	0.176	6.40
1.5	0.707	0.215	6.40
2	0.816	0.249	6.40
10	1.833	0.559	3.99
20	2.6	0.792	2.81
30	3.192	0.973	2.29
50	4.136	1.261	1.77
88	5.516	1.681	1.33
100	5.889	1.795	1.24
108	6.125	1.867	1.19
150	7.25	2.21	1.01
174	7.825	2.385	0.93
200	8.408	2.563	0.87
300	10.373	3.162	0.71
400	12.051	3.673	0.61
450	12.817	3.906	0.57
500	13.545	4.128	0.54
512	13.715	4.18	0.53
600	14.909	4.544	0.49
700	16.175	4.93	0.45
800	17.362	5.292	0.42
824	17.637	5.376	0.41
894	18.42	5.614	0.40
960	19.134	5.832	0.38
1000	19.556	5.96	0.37
1250	22.044	6.719	0.33
1500	24.326	7.414	0.30
1700	26.038	7.936	0.28
1800	26.862	8.187	0.27
2000	28.455	8.673	0.26
2100	29.227	8.908	0.25
2200	29.984	9.139	0.24
2300	30.727	9.365	0.24
2500	32.174	9.806	0.23
2700	33.576	10.233	0.22
3000	35.602	10.851	0.21
3400	38.183	11.638	0.19
3700	40.041	12.204	0.18
4000	41.841	12.753	0.17
5000	47.5	14.477	0.15
6000	52.747	16.077	0.14
8000	62.37	19.01	0.12
8800	65.974	20.108	0.11
10000	71.173	21.693	0.10
12000	79.393	24.198	0.09
14000	87.172	26.569	0.08
15800	93.872	28.611	0.08
16000	94.601	28.833	0.08
18000	101.745	31.01	0.07

www.commscope.com/andrew

©2011 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope. All specifications are subject to change. See www.commscope.com/andrew for the most current information.

page 3 of 4
2/7/2011

Product Specifications

FSJ1-50A



Regulatory Compliance/Certifications

Agency

UL/ETL Certification
RoHS 2002/95/EC
China RoHS SJ/T 11364-2006
ISO 9001:2008

Classification

Compliant
Compliant
Below Maximum Concentration Value (MCV)
Designed, manufactured and/or distributed under this quality management system



www.commscope.com/andrew

©2011 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope. All specifications are subject to change.
See www.commscope.com/andrew for the most current information.

page 4 of 4
2/7/2011